

TOP SCRUB

PURPOSE:

To remove a few layers of old floor finish and soil before recoating with new floor finish.

REQUIRED SUPPLIES & EQUIPMENT:

- Autoscrubber or floor machine with blue pad
- Wet pick up vacuum
- 2 mop buckets with wringers
- 2 wet mop handles with wet mops
- Set of 'wet floor' signs
- Hand pads and holder
- Putty knife
- Dust mop
- Dust pan and brush
- Doorway mats
- Approved deep scrub concentrate



PROCEDURE #5:

- Prepare equipment – Fill mop buckets with water, add proper amount of deep scrub concentrate to one. Transport to work site.
- Prepare area—Set up “Wet Floor” signs. Select an area of about 200 square feet. Place mats so that soiled shoes can be wiped off instead of tracking dirt into the area being cleaned.
- Dust mop floor—Follow procedure #1. Use clean dust mop.
- Wet Floor—Generously spread the floor scrub solution over the area with one mop. Allow the solution to set on the floor for the recommended time. Do not allow to dry.
- Automatic or machine scrub—Place blue pad under machine. Scrub area and keep wet. Use hand pad to scrub along edges of area. Avoid splashing walls.
- Pick up dirty solution—Use wet pick-up vacuum or automatic scrubber. Do not allow dirty solution to dry on the floor.
- Rinse and dry floor—Using clean mop and clean water. Cover area liberally with rinse water. Pick up rinse water with vacuum or automatic scrubber. Wipe baseboards.